



HOUSING: SCHEDULE 40 (S.S.) OR SCHEDULE 80 PVC
 END CONNECTIONS:
 F – FLANGED: 150LB (ANSI B16.5)
 T – NPT THREAD, AVAILABLE SIZE 1" – 4" ONLY
 MIXING ELEMENTS: 4 (FOUR)
 INJECTOR: 20 MICRON POROUS
 T316 STAINLESS STEEL (REMOVABLE)

DOWNSTREAM END VIEW

TABULATION BLOCK					
PIPE SIZE NPS	S1 NPT SIDE COUPLING	S2 NPT GAS INPUT CONN.	L1 in.	L2 in.	DESIGN FLOW, gpm ($\Delta P = 3.5$ psi) ALLOWS 50% TURNDOWN
1	1/4	1/8	13	3 1/2	15
1 1/2	1/4	1/8	18	4 1/4"	33
2	1/2	3/8	24	4 1/4	60
2 1/2	1/2	3/8	30	6 1/4	92
3	1/2	3/8	36	3	130
4	3/4	1/2	48	4	235
6	3/4	1/2	72	6	530
8	3/4	1/2	96	7	940
10	1	3/4	120	8	1470
ALL DIMENSIONS ARE IN INCHES					

KOMAX® SYSTEMS, INC.
 P.O. BOX 1323 WILMINGTON, CA 90748-1323 213-830-4320 FAX: 213-830-9826

OUTLINE & MOUNTING CONFIGURATION

STANDARD KOMAX OZONE MIXER
 AVAILABLE IN S.S., PVC, FRP & OTHER MATERIAL

SCALE: 60 = 1"	APPROVED:	DRAWN BY: EA
DATE: 12-10-07		REV. DATE:
CUSTOMER:	QUOTE NO.:	CODE#
	JOB NO.:	004-29
		DRAWING NUMBER: PROPOSA